

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

Regulation (EU) n. 2020/878

Master item code: 101871-

Safety Data Sheet date: 9/9/2022, version 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SOCOSAT SDS70/30 (TP2)
SDS code: P33202
References: SOCOSAT SDS24 70/30 ; SOCOSAT SDS850 70/30
UFI: 6SV6-3P3R-U238-NN40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Disinfectant
General public
Professional uses
Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

Ireland - National Poisons Information Centre: 01 8092166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to hazardous or special waste collection point.

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

Additional information in accordance with Article 25 of the CLP Regulation:

As stipulated in the CLP (Section 25) and OPI (Section 69) regulations, the indications on the label must be clearly legible. In accordance with Article 35 of the REACH Regulation, the safety data sheet must be provided to all employees.

a) Identity of each active substance and its concentration in metric units:

See section 15

b) Nanomaterials present in the product:

Contains no nanomaterials.

c) Authorisation number:

This biocidal product is concerned by the transitional period according to Article 89 of the BPR Regulation.

d) Name and address of the authorisation holder: see Section 1.3

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

- e) Type of formulation: liquid solution impregnated on wipes, soluble concentrate
- f) Planned or authorized applications : see section 15
- g) Instructions for use, frequency of application and rate to be applied:
See Technical Data Sheet
- (h) Indications of possible direct or indirect undesirable side effects and first aid instructions:
First aid instructions, see section 4.
- (i) Instructions, where appropriate, on warnings for vulnerable groups :
A brochure will not be created because all the information required for the industrial user are indicated in the safety data sheet.
- j) Instructions for safe disposal of the biocidal product: see section 13
- k) Batch number or designation of the preparation and expiry date in normal storage conditions :
See label
- l) Additional information where appropriate:
Not applicable
- m) Categories of users to which the biocidal product is restricted:
General public
Professional users
Industrial users
- n) Where appropriate, information on any specific risks to the environment, by to protect non-target organisms and avoid water contamination:
See section 12

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification	
>= 50% - < 60%	ethanol; ethyl alcohol	Index number: CAS: EC: REACH No.:	603-002-00-5 64-17-5 200-578-6 01-	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

		2119457610 -43	
>= 0.5% - < 1%	butanone; ethyl methyl ketone	Index number: CAS: EC: REACH No.: 01- 2119457290 -43	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H336 EUH066

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Burning sensation.

Swelling

Blurred vision.

Tearing.

Swollen eyelids.

Itching.

Repeated exposure may cause skin dryness or cracking.

If swallowed, aspiration into the lungs may occur and cause a chemical pneumonia.

Vapours may cause drowsiness and dizziness.

Headache

Nausea

Loss of coordination.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water

Foam.

Multipurpose powders class ABC

Powders class BC

Carbon dioxide (CO₂)

In case of fire, use a CO₂ fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

7.2. Conditions for safe storage, including any incompatibilities

Store under the same conditions as a combustible solid product.

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

ethanol; ethyl alcohol - CAS: 64-17-5

- OEL Type: EU - TWA(8h): 960 mg/m³, 500 ppm - Notes: GERMANY - AGW (BAuA - TRGS 900, 21/06/2010)

- OEL Type: EU - TWA(8h): 1900 mg/m³, 1000 ppm - STEL: 9500 mg/m³, 5000 ppm - Notes: FRANCE (INRS - ED984 : 2012) - TMP N°84

- OEL Type: ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr

- OEL Type: National - TWA: 1000 ppm - Notes: UK

- OEL Type: National - TWA: 1907 mg/m³, 1000 ppm - Notes: Belgique

butanone; ethyl methyl ketone - CAS: 78-93-3

- OEL Type: National - TWA: 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm - Notes: France VLEC

- OEL Type: EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

- OEL Type: National - TWA: 600 mg/m³, 200 ppm - Notes: AGW, Germany

- OEL Type: MAK - TWA: 295 mg/m³, 100 ppm - STEL(30min (Miw)): 590 mg/m³, 200 ppm - Notes: Österreich

DNEL Exposure Limit Values

ethanol; ethyl alcohol - CAS: 64-17-5

Worker Industry: 1900 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects - Notes: 1000ppm

Worker Industry: 950 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects - Notes: 500ppm

Worker Industry: 343 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

butanone; ethyl methyl ketone - CAS: 78-93-3

Worker Industry: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human Dermal - Frequency: Short Term (acute) - Notes: 1 day

Worker Industry: 600 mg/m³ - Consumer: 106 mg/m³ - Exposure: Human Inhalation -

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

Frequency: Short Term (acute)

Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Short Term (acute)

PNEC Exposure Limit Values

ethanol; ethyl alcohol - CAS: 64-17-5

Target: Fresh Water - Value: 0.96 mg/l

Target: Marine water - Value: 0.79 mg/l

Target: Freshwater sediments - Value: 3.6 mg/kg dw

Target: Marine water sediments - Value: 2.9 mg/kg dw

Target: Soil (agricultural) - Value: 0.63 mg/kg dw

Target: PNEC Oral (foodstuff) - Value: 0.72 g/kg

butanone; ethyl methyl ketone - CAS: 78-93-3

Target: Fresh Water - Value: 55.8 mg/l

Target: Marine water - Value: 55.8 mg/l

Target: Freshwater sediments - Value: 284.74 mg/kg

Target: Marine water sediments - Value: 287.7 mg/kg

Target: Soil (agricultural) - Value: 22.5 mg/kg

Biological Exposure Index

N.A.

8.2. Exposure controls

Eye protection:

Safety goggles (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

In case of prolonged contact, use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

In case of prolonged contact and in the event of irritation, it is advised to wear protective gloves.

(PVC, neoprene or rubber)

Respiratory protection:

Use adequate protective respiratory equipment.

Filtering Half-face mask (NF EN 149), class FFP1

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOSAT SDS70/30 (TP2)

Properties	Value	Method:	Notes
Physical state:	Liquid coated on wipes	--	--
Colour:	Colourless	--	--
Odour:	N.A.	--	--
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	Flam. Liq. 2, H225	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point (°C):	19	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	Not Relevant	--	--
Density and/or relative density:	< 1	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 74 %

Volatile Organic compounds - VOCs = 644 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Strong oxidizers.

Acids.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

ethanol; ethyl alcohol - CAS: 64-17-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 50 mg/m³

butanone; ethyl methyl ketone - CAS: 78-93-3

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation > 5000 ppm

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

Acute toxicity;

Skin corrosion/irritation;

Serious eye damage/irritation;

Respiratory or skin sensitisation;

Germ cell mutagenicity;

Carcinogenicity;

Reproductive toxicity;

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

STOT-single exposure;
STOT-repeated exposure;
Aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:
No endocrine disruptor substances present in concentration $\geq 0.1\%$

Other toxicological information:

butanone; ethyl methyl ketone
Skin corrosion / irritation (rabbit):
Slight irritating effect
Severe eye injury/irritation (rabbit):
Highly irritating

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ethanol; ethyl alcohol - CAS: 64-17-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Notes: *Leuciscus idus*

Endpoint: EC50 - Species: Algae = 275 mg/l - Duration h: 72 - Notes: *Chlorella vulgaris*

Endpoint: NOEC - Species: Algae = 3240 mg/l - Duration h: 120 - Notes: *Skeletonema costatum*

Endpoint: NOEC - Species: *Daphnia* = 9.6 mg/l - Duration h: 240 - Notes: *Ceriodaphnia dubia*

Endpoint: EC50 - Species: *Daphnia* = 857 mg/l - Duration h: 48 - Notes: *Artemia salina* nauplii

butanone; ethyl methyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: *Daphnia* = 13 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: *Oncorhynchus mykiss*

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 168 - Notes: *Desmodesmus subspicatus*

12.2. Persistence and degradability

ethanol; ethyl alcohol - CAS: 64-17-5

Biodegradability: Readily biodegradable

butanone; ethyl methyl ketone - CAS: 78-93-3

Biodegradability: Readily biodegradable - Duration: 28 days - %: 98 - Notes: aerobic

12.3. Bioaccumulative potential

ethanol; ethyl alcohol - CAS: 64-17-5

Log Pow -0.35

butanone; ethyl methyl ketone - CAS: 78-93-3

Log Pow 0.3

Log Kow 0.3

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 3175
IATA-UN Number: 3175
IMDG-UN Number: 3175

14.2. UN proper shipping name

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (ethanol; ethyl alcohol)
IATA-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (ethanol; ethyl alcohol)
IMDG-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (ethanol; ethyl alcohol)

14.3. Transport hazard class(es)

ADR-Class: 4.1
ADR - Hazard identification number: 40
IATA-Class: 4.1
IATA-Label: 4.1
IMDG-Class: 4.1

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
IMDG-EmS: F-A , S-I

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

14.6. Special precautions for user

ADR-Subsidiary hazards:	-
ADR-S.P.:	216 274 601
ADR-Transport category (Tunnel restriction code):	2 (E)
IATA-Passenger Aircraft:	445
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	448
IATA-S.P.:	A46
IATA-ERG:	3L
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category B
IMDG-Segregation:	-
Q.L.: 1K	
Q.E.: E2	

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

Restrictions related to the substances contained:

Restriction 75

Listed or in compliance with the following international inventories:

N.A.

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

SOCOSAT SDS70/30 (TP2)

This product is a product for biocidal use-Product types:

TP2 - Disinfectant not intended for direct applications to humans or animals

Active substance: Ethanol 73.2% (v/v) / 68.7% (w/w), CAS: 64-17-5, EC:200-578-6

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Eye Irrit. 2, H319	Calculation method

This document was prepared by a competent person who has received appropriate training.
Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold
CCNL - Appendix 1
Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOSAT SDS70/30 (TP2)

ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.